



APRS SPLIT SERIES POWER PEDESTAL


MODEL NO.	RECEPTACLES		BREAKERS	
	QTY	TYPE	QTY	TYPE
APRS 3	1	15A Duplex	1	15A Single Pole
	1	30A 125V RV	1	30A Single Pole
APRS 3G	1	15A GFI Duplex	1	15A Single Pole
	1	30A 125V RV	1	30A Single Pole
APRS 3-20	1	15/20A Duplex	1	20A Single Pole
	1	30A 125V RV	1	30A Single Pole
APRS 3-20G	1	15/20A GFI Duplex	1	20A Single Pole
	1	30A 125V RV	1	30A Single Pole
APRS 8	1	15A Duplex	1	15A Single Pole
	1	50A 125/250V	1	50A Two Pole
APRS 8G	1	15A GFI Duplex	1	15A Single Pole
	1	50A 125/250V	1	50A Two Pole
APRS 8-20	1	15/20A Duplex	1	20A Single Pole
	1	50A 125/250V	1	50A Two Pole
APRS 8-20G	1	15/20A GFI Duplex	1	20A Single Pole
	1	50A 125/250V	1	50A Two Pole
APRS 9	1	30A 125V RV	1	30A Single Pole
	1	50A 125/250V	1	50A Two Pole
APRS 10	1	15A Duplex	1	15A Single Pole
	1	30A 125V RV	1	30A Single Pole
	1	50A 125/250V	1	50A Two Pole
APRS 10G	1	15A GFI Duplex	1	15A Single Pole
	1	30A 125V RV	1	30A Single Pole
	1	50A 125/250V	1	50A Two Pole
APRS 10-20	1	15/20A Duplex	1	20A Single Pole
	1	30A 125V RV	1	30A Single Pole
	1	50A 125/250V	1	50A Two Pole
APRS 10-20G	1	15/20A GFI Duplex	1	20A Single Pole
	1	30A 125V RV	1	30A Single Pole
	1	50A 125/250V	1	50A Two Pole

FEATURES AND BENEFITS


- Mainly used in campgrounds and larger amperage applications
- **Split configuration to allow lower amperage feeds**
- Most robust pedestal design with thickest baseplate in class and fully welded design
- Fully customizable design with large selection of options
- Splitter bars allow single securing point or customized feed-thru capabilities
- Padlockable cover for maximum security
- Multiple base configurations with the padmount being the standard
- Magnetic breakers enable branch rated protection
- Fully secured using anchor bolts set in concrete base
- Heavy duty construction
- ASA-61 grey industrial powder coat finish
- Feed-thru splitter blocks available
- Custom heights available
- Custom colours available

TECHNICAL INFORMATION


- CSA Type 3R enclosure (weatherproof)
- 10" x 10" baseplate constructed of 1/4" mild steel
- Optional direct burial spade 28"H (26" below grade) 14 ga. galvanized steel spade
- 34 1/2"H x 6"W x 4"D body constructed of 12 ga. mild steel
- 14 1/4"H x 5 3/4" backpan constructed of 14 ga. galvaneal steel
- Standard qty. 3 B125 splitter blocks (#14 to 1/0 primary; #14 to #2 secondary)
- Grounding lug for 1/0 to #14 AWG wire
- 10KAIR branch rated breakers




APRS-3



APRS-8



APRS-9



APRS-10

ACE MANUFACTURING METALS LTD

Toll Free (866) 352-7145 · Direct (780) 352-7145 · BC Direct (250) 808-9116

www.acemfg.com · info@acemfg.com · Fax (780) 352-7147