



APR TOP LIGHT POWER PEDESTALS

FEATURES AND BENEFITS

- EEMAC/CEMA Type 3R Enclosure (Weatherproof)
- Heavy duty construction
- Padlockable cover for maximum security
- Built in docking light feature c/w light control (photocell) for efficient illumination
- Various splitter configurations available to suit your specific application
- Fully customizable design (see options below)
- Industry standard ASA-61 grey industrial powder coat finish
- Custom colors available (consult factory)
- Standard template and anchor bolts supplied



TECHNICAL INFORMATION

- 10" x 10" baseplate constructed of 1/4" THK mild steel
- 34 1/2"H x 6"W x 4"D body constructed of 12 ga. mild steel
- 14 1/4"H x 5 3/4"W backpan constructed of 14 ga. mild steel
- Standard Qty. 3 B125 splitter bars (125A primary; 70A branch); Higher amperage blocks available
- Qty. 1 grounding lug
- Fully welded base
- Durable high impact housing on photocell
- 75 Watt Top Light fixture

Custom Pedestal Ordering

APR-CXYYYY-ZZZ

OPTION GROUP (Z)

TL	Top Light
PH	Photocell

RECEPTACLE TYPES (Y)

1	15A Duplex
A	15A TL
2	15/20A Duplex
B	20A TL
3	30A
C	30A TL
5	50A
G	15A GFI Duplex

X = # of receptacles
Y = receptacle type
(4 max.)
Z = Option Group

